

# HM Trend

## ACCESSORIES

The hydraulic module simplifies the integration of air source heat pumps into the system hydraulics and is equipped with an appliance cover with high quality paint finish. This allows many components to be installed directly in a single step. The heat pump manager, high efficiency heating circuit pump for heating and DHW, safety valve, expansion vessel and emergency/auxiliary heater are all integrated as standard. An optional insulated connector block can be used, which simplifies installation and reduces installation time.

### The main features

For simplified installation of air source heat pumps

---

Compact design for a small footprint

---

High equipment level through prefabricated hydraulic components

---

Ideal for use in family homes

PRODUCT-NO.: 232805



**HMS Trend**

Product-No.: 233826



Type	HM Trend	HMS Trend
Part no.	232805	233826

## Technical data

Max. permissible pressure	0.30 MPa	0.30 MPa
External available pressure differential at 1.0 m <sup>3</sup> /h	715 hPa	715 hPa
External available pressure differential at 1.5 m <sup>3</sup> /h	661 hPa	661 hPa
External available pressure differential at 2 m <sup>3</sup> /h	468 hPa	468 hPa
External available pressure differential at 2.5 m <sup>3</sup> /h	300 hPa	300 hPa
Expansion vessel volume	24 l	24 l
Rated voltage, control unit	230 V	230 V
Rated voltage, emergency/auxiliary heater	400 V	230 V
Power consumption, emergency/auxiliary heater	8.80 kW	5.90 kW
Height	896 mm	896 mm
Height incl. connector block	1131 mm	1131 mm
Width	590 mm	590 mm
Depth	405 mm	405 mm
Weight	27 kg	27 kg
Connection	G 1	G 1

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.