

UPF 30/1-12 E

PRODUCT-NO.: 235053

Energy efficient brine circuit pump (EEI ≤ 0.23), electronically controlled, with vapour diffusion-proof thermal insulation.

The main features

with connecting cable





Type	UPF 30/1-8 E	UPF 30/1-12 E	UPF 40/1-8 E
Part no.	232532	235053	227413

Technical data

Energy Efficiency Index EEI	0.23	0.23	0.23
Connection	G 2	G 2	DN 40
Delivery head	8.00 m	12.00 m	8.00 m
Max. flow rate	8.00 m ³ /h	10.00 m ³ /h	15.00 m ³ /h
Power consumption	8-130 W	16-310 W	12-310 W
Rated voltage	230 V	230 V	230 V
Control via 0-10 V signal with IF module	-	-	-
Control via differential pressure	x	x	x
Control via PWM signal	-	-	-
Installation length (centre distance)	180 mm	180 mm	220 mm



Type	UPF 50/1-12 E
------	---------------

Part no.	227414
----------	--------

Technical data

Energy Efficiency Index EEI	0.23
-----------------------------	------

Connection	DN 50
------------	-------

Delivery head	12.00 m
---------------	---------

Max. flow rate	29.00 m ³ /h
----------------	-------------------------

Power consumption	25-590 W
-------------------	----------

Rated voltage	230 V
---------------	-------

Control via 0-10 V signal with IF module	-
--	---

Control via differential pressure	x
-----------------------------------	---

Control via PWM signal	-
------------------------	---

Installation length (centre distance)	280 mm
---------------------------------------	--------

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.