

UPF 50/1-12 E

ACCESSORIES

Energy efficient brine circuit pump (EEI ≤ 0.23), electronically controlled, with vapour diffusion-proof thermal insulation.

The main features

Circulation pump with thermal insulation

Electronic closed-loop control

Insulation shell included in delivery

PRODUCT-NO.: 227414



UPF 30/1-8 E

Product-No.: 232532



UPF 40/1-8 E

Product-No.: 227413



Type	UPF 30/1-8 E	UPF 40/1-8 E	UPF 50/1-12 E
Part no.	232532	227413	227414

Technical data

Energy Efficiency Index EEI	0.23	0.23	0.23
Connection	G 2	DN 40	DN 50
Delivery head	8.00 m	8.00 m	12.00 m
Max. flow rate	8.00 m ³ /h	15.00 m ³ /h	29.00 m ³ /h
Power consumption	8-130 W	12-310 W	25-590 W
Rated voltage	230 V	230 V	230 V
Control via 0-10 V signal with IF module	-	-	-
Control via differential pressure	x	x	x
Control via PWM signal	-	-	-
Installation length (centre distance)	180 mm	220 mm	280 mm

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.