WPKI-HKM 24 DN 25

ACCESSORIES

PRODUCT-NO.: 206300

The main features

Pump assembly for heating circuit with mixer

Including thermal insulation and wall mounting bracket

Complete with built-in high efficiency pump and 24 V mixer motor

WPKI-HKM 24 DN 32
Product-No.: 206628

WPKI-HKM 24 DN 40
Product-No.: 206632

Type	WPKI-HKM 24 DN 25	WPKI-HKM 24 DN 32	WPKI-HKM 24 DN 40
Part no.	206300	206628	206632

Technical data

Connection, above	G 1	G 1 1/4 I	1 1/2 I
Connection, below	G 1 1/2 A	G 2 A	DN 40 PN6
Circulation pump type	Wilo Para SC 25/6-43	Grundfos UPML 32-105 AUTO	Wilo Yonos MAXO plus 40/0.5-12
Height	383 mm	441 mm	811 mm
Width	250 mm	250 mm	320 mm
Depth	245 mm	293 mm	554 mm
Energy Efficiency Index EEI	0.20	0.20	0.20
Delivery head	6.70 m	10.00 m	12.00 m
Max. flow rate	6.00 m³/h	11.40 m³/h	17.70 m³/h

Contact information

You have questions? We appreciate to help you:
Call **+49 5531 - 7020**
Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.