




HPA-0 7 S Premium







AIR-WATER HEAT PUMPS

PRODUCT-NO.: 238976













Obligatory supplies

Article	Part no.	Type	Description
	233622	<u>AS-WP 1</u>	Hydraulic connection set, Connection: 32 x 2.9 mm
	233623	<u>AS-WP 2</u>	Hydraulic connection set, Connection: G 1 1/4
	236000	<u>WPM International</u>	Heat pump manager with international operating instructions, Height: 400 mm, Width: 310 mm, Depth: 100 mm

Additional supplies

Article	Part no.	Type	Description
	233711	STB-FB	Safety thermostat, underfloor heating system
	233603	<u>WPKI-HKM E</u>	Heating circuit assembly with mixing valve
	233602	<u>WPKI-HK E</u>	Heating circuit assembly without mixing valve
	232805	<u>HM Trend</u>	Hydraulic module
	234722	<u>WK 2</u>	Wall mounting panel
	233831	<u>SD 32-2 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 32, Length: 2 m, External diameter with insulation: 106 mm,

Connections for the heating and source side:
G 1 1/4

	235950	<u>UP 25/1-8 PCV</u>	Circulation pump
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Energy efficiency class: A
	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Energy efficiency class: C
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	234763	<u>WPKI 5</u>	Compact installation
	234764	<u>BBI 5</u>	Compact installation
	233510	<u>HSBC 200</u>	Integral cylinder, Nominal capacity, DHW cylinder: 168 l, Nominal capacity, buffer cylinder: 100 l, Energy efficiency class: B
	233010	<u>HM</u>	Hydraulic module
	232964	<u>SK 1</u>	T-support with 1 m long ribbon heater
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	232979	<u>HZB-2</u>	Ribbon heater 2 m, Rated voltage: 230 V, Power supply: 1/N/PE
	232978	<u>HZB-1</u>	Ribbon heater 1 m, Rated voltage: 230 V, Power supply: 1/N/PE

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.