





LWZ 5 S Plus






CENTRAL












PRODUCT-NO.: 201291

Obligatory supplies

Article	Part no.	Type	Description
	227664	<u>FES Comfort</u>	Comfort programming unit for wall mounting
	229336	<u>ISG web</u>	Internet Service Gateway
	239572	VLR 70-8 CU	Control set for 2 ventilation units
	233836	<u>AWG 315 SR</u>	Wall outlet with weather grille, thermally insulated, Internal diameter: 315 mm
	201720	<u>LSWP 315-1.5 SG</u>	Thermally and sound insulated air hose, 1.5 m long, DN 315, grey outer sheath, Internal diameter: 315 mm

Additional supplies

Article	Part no.	Type	Description
	227665	<u>{LSK Inverter}</u>	Summer cassette
	233301	ZLWZ circulation set	Connection set for DHW circulation pump, Internal diameter: 12 mm
	233867	<u>{LWTF Inverter}</u>	Replacement enthalpy heat exchanger
	232955	<u>AWG 315 GL</u>	Grey painted wall transition with weather grille, thermally insulated, Internal diameter: 315 mm
	231330	<u>FMS G4-10 ABL inverter</u>	Filter mat set for extract air G4, 10 pce

	227664	<u>FES Comfort</u>	Comfort programming unit for wall mounting
	231332	<u>FMK F7-2 ZUL Inverter</u>	Filter mat set for supply air F7, 2 pce
	232675	<u>LULH 315 o</u>	Air diverter hood, outdoor/exhaust air
	229336	<u>ISG web</u>	Internet Service Gateway
	233836	<u>AWG 315 SR</u>	Wall outlet with weather grille, thermally insulated, Internal diameter: 315 mm
	231039	<u>AWG 315 L</u>	Wall outlet for light shaft, thermally insulated, Internal diameter: 315 mm
	231331	<u>FMS M5-2 ZUL inverter</u>	Filter mat set for supply air M5, 2 pce
	201720	<u>LSWP 315-1.5 SG</u>	Thermally and sound insulated air hose, 1.5 m long, DN 315, grey outer sheath, Internal diameter: 315 mm
	234646	<u>LSWP 315-4 S</u>	Thermally and sound insulated air hose, 4 m long, DN 315, Internal diameter: 315 mm, Length: 4 m
	201618	<u>LSWP 315-4 SG</u>	Thermally and sound insulated air hose, 4 m long, DN 315, grey outer sheath, Internal diameter: 315 mm, Length: 4 m
	233485	<u>ZLWZ Trans</u>	Transport aid

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.