

WPL 19 A









AIR-WATER HEAT PUMPS

PRODUCT-NO.: 236412

Obligatory supplies

Article	Part no.	Type	Description
	239572	VLR 70-8 CU	Control set for 2 ventilation units

Additional supplies

Article	Part no.	Type	Description
	235199	<u>SBPE 400</u>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	233010	<u>HM</u>	Hydraulic module
	234350	<u>SBBE 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Energy efficiency class: B, Depth: 852 mm, Height: 1972 mm, Width: 786 mm
	234351	<u>SBBE 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Energy efficiency class: B, Width: 786 mm, Height: 1972 mm, Depth: 852 mm
	235950	<u>UP 25/1-8 PCV</u>	Circulation pump
	234763	<u>WPKI 5</u>	Compact installation
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Energy efficiency class: A
	233602	<u>WPKI-HK E</u>	Heating circuit assembly without mixing valve

	227534	<u>SBB 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Energy efficiency class: C, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Energy efficiency class: C
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	185459	<u>SBP 700 E</u>	Buffer cylinder, Rated capacity: 720 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	233510	<u>HSBC 200</u>	Integral cylinder, Nominal capacity, DHW cylinder: 168 l, Nominal capacity, buffer cylinder: 100 l, Energy efficiency class: B
	234764	<u>BBI 5</u>	Compact installation
	234349	<u>SBBE 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Energy efficiency class: A
	221361	<u>SBB 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Energy efficiency class: C
	221362	<u>SBB 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Energy efficiency class: C, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	233603	<u>WPKI-HKM E</u>	Heating circuit assembly with mixing valve
	220824	<u>SBP 400 E</u>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	230013	<u>HZEA</u>	Softening device for heating systems, Height: 600 mm, Width: 260 mm, Depth: 130 mm



185458

SBP 200 E

Buffer cylinder, Rated capacity: 207 l, Height:
1535 mm, Diameter incl. thermal insulation:
630 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.