



WPL 19 I






AIR-WATER HEAT PUMPS















PRODUCT-NO.: 235193







Obligatory supplies








Article	Part no.	Type	Description
	239572	VLR 70-8 CU	Control set for 2 ventilation units
	201721	LSWP 560-3 SG	Thermally and sound insulated air hose, 3.0 m long, DN 560, grey outer sheath, Length: 3 m
	233837	<u>AWG 560 H-SR</u>	Wall outlet with weather grille, thermally insulated

Additional supplies

Article	Part no.	Type	Description
	231930	<u>WDH 1500 SBP</u>	Thermal insulation, Standby energy consumption/24 h at 65 °C: 4,1 kWh, Insulation for: SBP 1500 E and E SOL, Thickness: 110 mm, Height: 2255 mm
	233831	<u>SD 32-2 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 32, Length: 2 m, External diameter with insulation: 106 mm, Connections for the heating and source side: G 1 1/4
	232957	<u>AWG 560 V-GL</u>	Grey painted wall transition with weather grille, thermally insulated
	232956	<u>AWG 560 H-GL</u>	Grey painted wall transition with weather grille, thermally insulated
	227420	<u>HUV 1</u>	Heating diverter valve, Connection: G1

	233828	<u>SD 25-2 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	229286	<u>PK 10</u>	Condensate pump with hose connection, Max. head: 5 m, Max. pump rate: 500 l/h
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	233602	<u>WPKI-HK E</u>	Heating circuit assembly without mixing valve
	233838	<u>AWG 560 V-SR</u>	Wall outlet with weather grille, thermally insulated
	231044	<u>AWG 600 L</u>	Wall outlet with weather grille, thermally insulated
	234762	<u>WPKI 6</u>	Compact installation
	234764	<u>BBI 5</u>	Compact installation
	235950	<u>UP 25/1-8 PCV</u>	Circulation pump
	230381	<u>WPM-RBS</u>	Relay set for high efficiency pumps, Height: 211 mm, Width: 205 mm, Depth: 56 mm
	230031	<u>HZEN</u>	Refill cartridge for softening device
	231929	<u>WDH 1000 SBP</u>	Thermal insulation, Standby energy consumption/24 h at 65 °C: 3,6 kWh, Insulation for: SBP 1000 E and E SOL, Height: 2340 mm, Thickness: 110 mm
	230013	<u>HZEA</u>	Softening device for heating systems, Height: 600 mm, Width: 260 mm, Depth: 130 mm
	234647	<u>LSWP 560-4 S</u>	Sound-optimised air hose, 4 m long, DN 560, Length: 4 m

	233603	<u>WPKI-HKM E</u>	Heating circuit assembly with mixing valve
	233837	<u>AWG 560 H-SR</u>	Wall outlet with weather grille, thermally insulated
	232971	<u>SD 25-2.5 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2.5 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	227534	<u>SBB 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Energy efficiency class: C, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Energy efficiency class: C
	185459	<u>SBP 700 E</u>	Buffer cylinder, Rated capacity: 720 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	231041	<u>AWG 560 L</u>	Wall outlet for light shaft, thermally insulated
	233510	<u>HSBC 200</u>	Integral cylinder, Nominal capacity, DHW cylinder: 168 l, Nominal capacity, buffer cylinder: 100 l, Energy efficiency class: B
	185460	<u>SBP 700 E SOL</u>	Buffer cylinder, Rated capacity: 703 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	229336	<u>ISG web</u>	Internet Service Gateway
	236686	<u>HSBC 300 cool</u>	Integral cylinder, Nominal capacity, DHW cylinder: 270 l, Nominal capacity, buffer cylinder: 100 l, Energy efficiency class: B
	232805	<u>HM Trend</u>	Hydraulic module
	221361	<u>SBB 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Energy efficiency class: C

	221362	<u>SBB 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Energy efficiency class: C, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	234763	<u>WPKI 5</u>	Compact installation
	233711	STB-FB	Safety thermostat, underfloor heating system
	220824	<u>SBP 400 E</u>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	227564	<u>SBP 1000 E</u>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227565	<u>SBP 1500 E</u>	Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.