

WPL 24 IK




AIR-WATER HEAT PUMPS

PRODUCT-NO.: 235879

Obligatory supplies













Article	Part no.	Type	Description
	233838	<u>AWG 560 V-SR</u>	Wall outlet with weather grille, thermally insulated
	231041	<u>AWG 560 L</u>	Wall outlet for light shaft, thermally insulated
	232956	<u>AWG 560 H-GL</u>	Grey painted wall transition with weather grille, thermally insulated
	233837	<u>AWG 560 H-SR</u>	Wall outlet with weather grille, thermally insulated
	232957	<u>AWG 560 V-GL</u>	Grey painted wall transition with weather grille, thermally insulated

Additional supplies

Article	Part no.	Type	Description
	235199	<u>SBPE 400</u>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	233831	<u>SD 32-2 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 32, Length: 2 m, External diameter with insulation: 106 mm, Connections for the heating and source side: G 1 1/4
	233828	<u>SD 25-2 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2 m, External diameter with insulation: 99 mm,

Connections for the heating and source side:
G 1 1/4

	234350	<u>SBBE 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Energy efficiency class: B, Depth: 852 mm, Height: 1972 mm, Width: 786 mm
	233711	STB-FB	Safety thermostat, underfloor heating system
	233603	<u>WPKI-HKM E</u>	Heating circuit assembly with mixing valve
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	234351	<u>SBBE 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Energy efficiency class: B, Width: 786 mm, Height: 1972 mm, Depth: 852 mm
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Energy efficiency class: A
	234762	<u>WPKI 6</u>	Compact installation
	232971	<u>SD 25-2.5 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2.5 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	234349	<u>SBBE 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Energy efficiency class: A
	233602	<u>WPKI-HK E</u>	Heating circuit assembly without mixing valve
	227534	<u>SBB 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Energy efficiency class: C, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Energy efficiency class: C

	229336	<u>ISG web</u>	Internet Service Gateway
	185459	<u>SBP 700 E</u>	Buffer cylinder, Rated capacity: 720 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	230031	<u>HZEN</u>	Refill cartridge for softening device
	238826	<u>HSBC 300 L cool</u>	Integral cylinder, Nominal capacity, DHW cylinder: 270 l, Nominal capacity, buffer cylinder: 100 l, Energy efficiency class: B
	185460	<u>SBP 700 E SOL</u>	Buffer cylinder, Rated capacity: 703 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	221361	<u>SBB 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Energy efficiency class: C
	229286	<u>PK 10</u>	Condensate pump with hose connection, Max. head: 5 m, Max. pump rate: 500 l/h
	221362	<u>SBB 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Energy efficiency class: C, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	220824	<u>SBP 400 E</u>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	230013	<u>HZEA</u>	Softening device for heating systems, Height: 600 mm, Width: 260 mm, Depth: 130 mm
	233719	<u>UPZ</u>	DHW circulation pump, Connection: G 1/2
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm



227564

SBP 1000 E

Buffer cylinder, Rated capacity: 1006 l, Height:
2300 mm, Diameter incl. thermal insulation:
1010 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.