


# WPL 57








AIR-WATER HEAT PUMPS


PRODUCT-NO.: 228837

## Obligatory supplies

Article	Part no.	Type	Description
	236000	<b><u>WPM International</u></b>	Heat pump manager with international operating instructions, Height: 400 mm, Width: 310 mm, Depth: 100 mm
	239572	<b>VLR 70-8 CU</b>	Control set for 2 ventilation units

## Additional supplies

Article	Part no.	Type	Description
	232908	<b><u>WTS 40 E</u></b>	Loading station, DHW heating, Height: 1090 mm, Width: 520 mm, Depth: 305 mm
	227423	<b><u>UP 50/1-12 E</u></b>	Circulation pump
	233711	<b>STB-FB</b>	Safety thermostat, underfloor heating system
	229295	<b><u>SBB 1001 SOL</u></b>	DHW cylinder, Rated capacity: 971 l, Diameter incl. thermal insulation: 1010 mm, Height: 2277 mm
	227589	<b><u>SBP 1500 E cool</u></b>	Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm
	236569	<b><u>SBP 1010 E</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	235951	<b><u>UP 30/1-8 PCV</u></b>	Circulation pump

	227422	<b><u>UP 40/1-8 E</u></b>	Circulation pump
	229293	<b><u>SBB 1001</u></b>	DHW cylinder, Rated capacity: 1004 l, Diameter incl. thermal insulation: 1010 mm, Height: 2277 mm
	227566	<b><u>SBP 1000 E SOL</u></b>	Buffer cylinder, Rated capacity: 979 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	236570	<b><u>SBP 1010 E cool</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227567	<b><u>SBP 1500 E SOL</u></b>	Buffer cylinder, Rated capacity: 1473 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm
	227564	<b><u>SBP 1000 E</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227588	<b><u>SBP 1000 E cool</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	229986	<b><u>SBS 1001 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 916 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm
	227565	<b><u>SBP 1500 E</u></b>	Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm
	229983	<b><u>SBS 1501 W</u></b>	Instantaneous water cylinder, Rated capacity: 1430 l, Height: 2155 mm, Diameter incl. thermal insulation: 1220 mm

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.