

# HPA-0 3 CS Plus flex Set S

PRODUCT-NO.: 238988

Set a new standard in new build Let's assume you're in the middle of building a detached house. You should take a look at this set. It makes use of advanced inverter technology to deliver a pleasingly high level of efficiency. Assured of the perfect supply With its high quality equipment features, this heat pump ensures that you have the best possible supply of DHW in your home at all times. The cooling function is included. You can therefore provide yourself and your family with a refreshing level of living comfort even on hot days. Install everything from one set We have already integrated a large proportion of the requisite system technology into the set, such as the hydraulic module and connecting components. This allows your installer to set up the appliance with minimal effort, without needing a lot of space.



## The main features

Inverter technology for high efficiency and low energy bills

Low operating noise; can be further reduced in night mode (silent mode function)

DHW and buffer cylinders from the STIEBEL ELTRON range can be added as required

Cooling function possible via area heating and fan convectors



Type	HPA-O 3 CS Plus flex Set S	HPA-O 4 CS Plus flex Set S	HPA-O 6 CS Plus flex Set S
Part no.	238988	238989	238990

## Technical data

Energy efficiency class, heat pump W35	A++	A++	A+++
Energy efficiency class, heat pump W55	A+	A+	A++
Energy efficiency class, composite system (heat pump + controller) W35	A++	A++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+	A+	A++
Heating output at A7/W35 (EN 14511)	2.73 kW	2.73 kW	4.86 kW
Heating output at A2/W35 (EN 14511)	2.08 kW	2.58 kW	5.30 kW
Heating output at A-7/W35 (EN 14511)	3.20 kW	3.96 kW	6.00 kW
Max. cooling capacity at A35/W7	2.00 kW	3.00 kW	5.00 kW
Cooling capacity at A35/W18 partial load	1.50 kW	1.50 kW	2.50 kW
Max. cooling capacity at A35/W18	2.00 kW	3.00 kW	5.00 kW
COP at A7/W35 (EN 14511)	4.70	4.70	4.76
COP at A2/W35 (EN 14511)	3.70	3.64	3.80
COP at A-7/W35 (EN 14511)	2.81	2.73	2.98
Max. energy efficiency ratio at A35/W7	2.15	1.62	1.73
Energy efficiency ratio at A35/W18 partial load	3.56	3.56	3.28
Max. energy efficiency ratio at A35/W18	3.12	3.12	2.88
SCOP (EN 14825)	4.23	4.15	4.50
Sound power level (EN 12102)	52 dB(A)	52 dB(A)	57 dB(A)
Min./max. application limits for heat source	-20...40 °C	-20...40 °C	-20...40 °C
Max. application limit on the heating side	60 °C	60 °C	60 °C

<b>Height</b>	740 mm	740 mm	812 mm
<b>Width</b>	1022 mm	1022 mm	1152 mm
<b>Depth</b>	524 mm	524 mm	524 mm
<b>Weight</b>	62 kg	62 kg	91 kg
<b>Rated voltage, compressor</b>	230 V	230 V	230 V
<b>Refrigerant</b>	R410A	R410A	R410A



Type	HPA-O 8 CS Plus flex Set S	HPA-O 3 CS Plus flex Set	HPA-O 4 CS Plus flex Set
Part no.	238991	239051	239052

## Technical data

Energy efficiency class, heat pump W35	A+++	A++	A++
Energy efficiency class, heat pump W55	A++	A+	A+
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A++	A++
Energy efficiency class, composite system (heat pump + controller) W55	A++	A+	A+
Heating output at A7/W35 (EN 14511)	4.86 kW	2.73 kW	2.73 kW
Heating output at A2/W35 (EN 14511)	5.30 kW	2.08 kW	2.58 kW
Heating output at A-7/W35 (EN 14511)	7.80 kW	3.20 kW	3.96 kW
Max. cooling capacity at A35/W7	6.00 kW	2.00 kW	3.00 kW
Cooling capacity at A35/W18 partial load	3.00 kW	1.50 kW	1.50 kW
Max. cooling capacity at A35/W18	6.00 kW	2.00 kW	3.00 kW
COP at A7/W35 (EN 14511)	4.76	4.70	4.70
COP at A2/W35 (EN 14511)	3.80	3.70	3.64
COP at A-7/W35 (EN 14511)	2.91	2.81	2.73
Max. energy efficiency ratio at A35/W7	1.73	2.15	1.62
Energy efficiency ratio at A35/W18 partial load	3.28	3.56	3.56
Max. energy efficiency ratio at A35/W18	2.88	3.12	3.12
SCOP (EN 14825)	4.50	4.23	4.15
Sound power level (EN 12102)	57 dB(A)	52 dB(A)	52 dB(A)
Min./max. application limits for heat source	-20...40 °C	-20...40 °C	-20...40 °C
Max. application limit on the heating side	60 °C	60 °C	60 °C

<b>Height</b>	812 mm	740 mm	740 mm
<b>Width</b>	1152 mm	1022 mm	1022 mm
<b>Depth</b>	524 mm	524 mm	524 mm
<b>Weight</b>	91 kg	62 kg	62 kg
<b>Rated voltage, compressor</b>	230 V	230 V	230 V
<b>Refrigerant</b>	R410A	R410A	R410A



Type	HPA-O 6 CS Plus flex Set	HPA-O 8 CS Plus flex Set
------	--------------------------	--------------------------

Part no.	239053	239054
----------	--------	--------

## Technical data

Energy efficiency class, heat pump W35	A+++	A+++
Energy efficiency class, heat pump W55	A++	A++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A++	A++
Heating output at A7/W35 (EN 14511)	4.86 kW	4.86 kW
Heating output at A2/W35 (EN 14511)	5.30 kW	5.30 kW
Heating output at A-7/W35 (EN 14511)	6.00 kW	7.80 kW
Max. cooling capacity at A35/W7	5.00 kW	6.00 kW
Cooling capacity at A35/W18 partial load	2.50 kW	3.00 kW
Max. cooling capacity at A35/W18	5.00 kW	6.00 kW
COP at A7/W35 (EN 14511)	4.76	4.76
COP at A2/W35 (EN 14511)	3.80	3.80
COP at A-7/W35 (EN 14511)	2.98	2.91
Max. energy efficiency ratio at A35/W7	1.73	1.73
Energy efficiency ratio at A35/W18 partial load	3.28	3.28
Max. energy efficiency ratio at A35/W18	2.88	2.88
SCOP (EN 14825)	4.50	4.50
Sound power level (EN 12102)	57 dB(A)	57 dB(A)
Min./max. application limits for heat source	-20...40 °C	-20...40 °C
Max. application limit on the heating side	60 °C	60 °C

<b>Height</b>	812 mm	812 mm
<b>Width</b>	1152 mm	1152 mm
<b>Depth</b>	524 mm	524 mm
<b>Weight</b>	91 kg	91 kg
<b>Rated voltage, compressor</b>	230 V	230 V
<b>Refrigerant</b>	R410A	R410A

Further information about the set components can be found under the respective product. The necessary T-support or wall mounting bracket is available as an accessory.

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.