

WPL 09 IKCS classic compact plus Set

AIR SOURCE HEAT PUMPS

PRODUCT-NO.: 236732

Bring all the efficiency indoors

You have near neighbours? No problem with this set of air source heat pump and combi unit consisting of a DHW and buffer cylinder. As the heat pump is installed indoors, noise or lack of space outdoors are not an issue. The sound insulation of the air ducts also contributes to this. The sound power level outdoors is roughly equivalent to the sound of a gentle breeze. If you opt to integrate your efficient heat pump into your home network, you can then conveniently control it via a smartphone or tablet.

Two cylinders in one

The cylinder requires little space in your utility room as it is a combi unit with two cylinders in one. Its capacity of 180 litres provides enough hot water for a shower or a relaxing bath. Your efficient heat pump will then keep your rooms comfortably warm – or cool in the summer.

The main features

Set consists of an indoor air source heat pump and integral cylinder for heating, cooling and hot water

Heat pump with inverter technology for high efficiency and low energy bills

Indoor installation ensures significantly lower outdoor noise, making it ideal for densely built-up areas

Flow temperature of up to 60 °C for high hot water convenience

Operating noise can be further reduced in night mode ("silent mode")

Integrated heat pump manager with intuitive menu guidance

Optional integration into the home network and control via smartphone (additional components required)



WPL 09 ICS classic compact plus Set

Product-No.: 236728



WPL 17 ICS classic compact plus Set

Product-No.: 236729



WPL 17 IKCS classic compact plus Set

Product-No.: 236733

Set-Components 1



Type	WPL 09 ICS classic	WPL 09 IKCS classic	WPL 17 ICS classic
Product set	WPL 09 ICS classic compact plus Set	WPL 09 IKCS classic compact plus Set	WPL 17 ICS classic compact plus Set

Technical data

Energy efficiency class, heat pump W35	A+++	A+++	A++
Energy efficiency class, heat pump W55	A++	A++	A++
SCOP 35 °C (EN 14825)	4.525	4.45	4.25
Heating output at A7/W35 (EN 14511)	2.06 kW	2.06 kW	4.27 kW
Heating output at A2/W35 (EN 14511)	2.64 kW	2.62 kW	5.02 kW
Heating output at A-7/W35 (EN 14511)	4.23 kW	4.18 kW	8.02 kW
Cooling capacity at A35/W18 partial load	1.85 kW	1.85 kW	3.60 kW
Max. cooling capacity at A35/W18	3.00 kW	3.00 kW	6.00 kW
COP at A7/W35 (EN 14511)	4.68	4.68	4.74
COP at A2/W35 (EN 14511)	3.83	3.76	3.83
COP at A-7/W35 (EN 14511)	3.16	3.07	2.63
Energy efficiency ratio at A35/W18 partial load	3.96	3.76	2.78
Energy efficiency ratio at A35/W18 max.	2.22	2.02	1.83
Sound power level (EN 12102)	45 dB(A)	45 dB(A)	51 dB(A)
Min./max. application limits for heat source	-20/35 °C	-20/35 °C	-20/35 °C
Max. application limit on the heating side	60 °C	60 °C	60 °C
Height	1381 mm	1892 mm	1381 mm
Width	874 mm	893 mm	874 mm

Depth	874 mm	833 mm	874 mm
Weight	173 kg	219 kg	175 kg
Refrigerant	R410A	R410A	R410A

Set-Components 1



Type	WPL 17 IKCS classic
Product set	WPL 17 IKCS classic compact plus Set

Technical data

Energy efficiency class, heat pump W35	A++
Energy efficiency class, heat pump W55	A++
SCOP 35 °C (EN 14825)	4.125
Heating output at A7/W35 (EN 14511)	4.22 kW
Heating output at A2/W35 (EN 14511)	4.95 kW
Heating output at A-7/W35 (EN 14511)	7.80 kW
Cooling capacity at A35/W18 partial load	3.60 kW
Max. cooling capacity at A35/W18	6.00 kW
COP at A7/W35 (EN 14511)	4.60
COP at A2/W35 (EN 14511)	3.70
COP at A-7/W35 (EN 14511)	2.58
Energy efficiency ratio at A35/W18 partial load	2.58
Energy efficiency ratio at A35/W18 max.	1.63
Sound power level (EN 12102)	50 dB(A)
Min./max. application limits for heat source	-20/35 °C
Max. application limit on the heating side	60 °C
Height	1892 mm
Width	893 mm

Depth	833 mm
Weight	221 kg
Refrigerant	R410A

Set-Components 2



Type	HSBC 200 L	HSBC 200 L	HSBC 200 L
Product set	WPL 09 ICS classic compact plus Set	WPL 09 IKCS classic compact plus Set	WPL 17 ICS classic compact plus Set

Technical data

Energy efficiency class	B	B	B
Standby energy consumption/24 h at 65 °C	1.30 kWh	1.30 kWh	1.30 kWh
Nominal capacity, DHW cylinder	180 l	180 l	180 l
Nominal capacity, buffer cylinder	100 l	100 l	100 l
Surface area, heat exchanger	1.60 m ²	1.60 m ²	1.60 m ²
Capacity, heat exchanger	10 l	10 l	10 l
Height	1908 mm	1908 mm	1908 mm
Width	680 mm	680 mm	680 mm
Depth	800 mm	800 mm	800 mm
Height when tilted	2107 mm	2107 mm	2107 mm
Weight	185 kg	185 kg	185 kg

Set-Components **2**

Type	HSBC 200 L
Product set	WPL 17 IKCS classic compact plus Set

Technical data

Energy efficiency class	B
Standby energy consumption/24 h at 65 °C	1.30 kWh
Nominal capacity, DHW cylinder	180 l
Nominal capacity, buffer cylinder	100 l
Surface area, heat exchanger	1.60 m ²
Capacity, heat exchanger	10 l
Height	1908 mm
Width	680 mm
Depth	800 mm
Height when tilted	2107 mm
Weight	185 kg

Further information about the Set components can be found under the respective product.

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.