

WPL 13 ACS classic compact set S

AIR | WATER HEAT PUMPS

PRODUCT-NO.: 239046

The main features

Comprising WPL 13 ACS classic + HSBB 200 S cylinder and hydraulic module

Little space is required

Buffer cylinder not required if the minimum flow rate is sufficient





Type	WPL 07 ACS classic compact set S	WPL 09 ACS classic compact set S	WPL 13 ACS classic compact set S
Part no.	236629	236632	239046

Technical data

Output at A2/W35 (EN 14511)	2,08 kW	2,59 kW	4,30 kW
Output at A-7/W35 (EN 14511)	3,20 kW	4,06 kW	6,00 kW
Coefficient of performance at A2/W35 (EN 14511)	3,75	3,72	3,97
Coefficient of performance at A-7/W35 (EN 14511)	2,81	2,72	2,92
Energy efficiency class, heat pump W35	A++	A++	A++
Energy efficiency class, W55 heat pump	A+	A+	A+
Energy efficiency class, composite system (heat pump + controller) W35	A++	A++	A++
Energy efficiency class, composite system (heat pump + controller) W55	A+	A+	A++
Cooling capacity at A35/W7 max.	2,00 kW	3,00 kW	5,00 kW
Cooling capacity at A35/W18 max.	2,00 kW	3,00 kW	5,00 kW
Cooling capacity at A35/W7 partial load	1,00 kW	1,50 kW	2,50 kW
Cooling capacity at A35/W18 partial load	1,50 kW	1,50 kW	2,50 kW
Sound power level (EN 12102)	52 dB(A)	52 dB(A)	57 dB(A)
Sound pressure level at 5 m distance in a free field	30 dB(A)	30 dB(A)	35 dB(A)
Rated compressor voltage	230 V	230 V	230 V
Max. application limit on the heating side	60 °C	60 °C	60 °C
Height	740 mm	740 mm	812 mm
Width	1022 mm	1022 mm	1152 mm
Depth	524 mm	524 mm	524 mm
Weight	62 kg	62 kg	91 kg



Type	WPL 17 ACS classic compact set S
Part no.	236635
Technical data	
Output at A2/W35 (EN 14511)	5,73 kW
Output at A-7/W35 (EN 14511)	7,80 kW
Coefficient of performance at A2/W35 (EN 14511)	3,97
Coefficient of performance at A-7/W35 (EN 14511)	2,92
Energy efficiency class, heat pump W35	A++
Energy efficiency class, W55 heat pump	A+
Energy efficiency class, composite system (heat pump + controller) W35	A++
Energy efficiency class, composite system (heat pump + controller) W55	A++
Cooling capacity at A35/W7 max.	6,00 kW
Cooling capacity at A35/W18 max.	6,00 kW
Cooling capacity at A35/W7 partial load	3,00 kW
Cooling capacity at A35/W18 partial load	3,00 kW
Sound power level (EN 12102)	57 dB(A)
Sound pressure level at 5 m distance in a free field	35 dB(A)
Rated compressor voltage	230 V
Max. application limit on the heating side	60 °C
Height	812 mm
Width	1152 mm
Depth	524 mm
Weight	91 kg

More details regarding set contents can be found under the relevant product

The necessary plinth or wall mounting bracket is available as an accessory

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.