



# WPL 13 basic








AIR | WATER HEAT PUMPS












PRODUCT-NO.: 230385

## Obligatory supplies

Article	Part no.	Type	Description
	234922	<b>WPMW 3 international</b>	Heat pump manager, Height: 215 mm, Width: 246 mm, Depth: 140 mm
	232980	<b>WPMW 3</b>	Heat pump manager, Height: 215 mm, Width: 246 mm, Depth: 140 mm

## Additional supplies

Article	Part no.	Type	Description
	230384	<b>ZVK-WPL...Basic A</b>	Casing, Colour: white
	234763	<b>WPKI 5</b>	Compact installation
	234764	<b>BBI 5</b>	Compact installation
	234348	<b><u>SBBE 301 WP</u></b>	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234349	<b><u>SBBE 302 WP</u></b>	DHW cylinder, Rated capacity: 290 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234921	<b>WPMS 3 international</b>	Heat pump manager, Height: 72 mm, Width: 146 mm, Depth: 96 mm
	235949	<b>UP 25/7.5 PCV</b>	Circulation pump
	235950	<b>UP 25/1-8 PCV</b>	Circulation pump

	232981	<b>WPMS 3</b>	Heat pump manager, Height: 72 mm, Width: 146 mm, Depth: 96 mm
	233602	<b>WPKI-HK E</b>	Heating circuit assembly without mixing valve
	233603	<b>WPKI-HKM E</b>	Heating circuit assembly with mixing valve
	165341	<b>AVF 6</b>	Contact sensor (PTC sensor), Length: 2 m
	185579	<b>FE 7</b>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	233711	<b>STB-FB</b>	Safety thermostat, underfloor heating system
	232974	<b>SD 25-1 KE</b>	Pressure hose (can be trimmed), angled, DN 25, 1 m with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	233828	<b>SD 25-2 GE</b>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	232971	<b>SD 25-2.5 GE</b>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2,5 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	074415	<b>SD 25-1</b>	Pressure hose, angled, with 19 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 80 mm, Connections for the heating and source side: G 1 1/4
	070633	<b>WT 10</b>	Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 99.6 mm

	221360	<b><u>SBB 301 WP</u></b>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221361	<b><u>SBB 302 WP</u></b>	DHW cylinder, Rated capacity: 290 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	233487	<b><u>SBB 300 WP Trend</u></b>	DHW cylinder, Rated capacity: 287 l, Height: 1652 mm, Diameter incl. thermal insulation: 650 mm
	233488	<b><u>SBB 400 WP Trend</u></b>	DHW cylinder, Rated capacity: 390 l, Diameter incl. thermal insulation: 750 mm, Height: 1565 mm
	185458	<b><u>SBP 200 E</u></b>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	185459	<b><u>SBP 700 E</u></b>	Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm
	229980	<b><u>SBS 601 W</u></b>	Instantaneous water cylinder, Rated capacity: 613 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229984	<b><u>SBS 601 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 599 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229981	<b><u>SBS 801 W</u></b>	Instantaneous water cylinder, Rated capacity: 759 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229985	<b><u>SBS 801 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 740 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.