


# WPL 13 E









AIR | WATER HEAT PUMPS
















PRODUCT-NO.: 227756












## Obligatory supplies



Article	Part no.	Type	Description
	236000	<b>WPM international</b>	Heat pump manager with international operating instructions, Height: 72 mm, Width: 146 mm, Depth: 96 mm









## Additional supplies

Article	Part no.	Type	Description
	201619	<b>LSWP 560-4 SG</b>	Sound-optimised air hose, 4 m long, DN 560, grey outer sheath, Length: 4 m
	201620	<b>UP 25/7.5 PCV</b>	Circulation pump, Connection: G 1 1/2
	074412	<b>ZVK-WPL 13/18/23 I</b>	Casing, Colour: white
	074413	<b>ZVK-WPL 13/18/23 A</b>	Casing, Colour: white
	233010	<b>HM</b>	Hydraulic module
	234763	<b>WPKI 5</b>	Compact installation
	234764	<b>BBI 5</b>	Compact installation
	234348	<b>SBBE 301 WP</b>	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm

	234349	<b><u>SBBE 302 WP</u></b>	DHW cylinder, Rated capacity: 290 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234350	<b><u>SBBE 401 WP SOL</u></b>	DHW cylinder, Rated capacity: 395 l, Depth: 852 mm, Height: 1972 mm, Width: 786 mm
	234351	<b><u>SBBE 501 WP SOL</u></b>	DHW cylinder, Rated capacity: 495 l, Height: 1972 mm, Width: 786 mm, Depth: 852 mm
	233510	<b><u>HSBC 200</u></b>	Integral cylinder, Nominal capacity, DHW cylinder: 168 l, Nominal capacity, buffer cylinder: 100 l, Depth: 871 mm, Height: 1908 mm, Width: 680 mm
	234647	<b>LSWP 560-4 S</b>	Sound-optimised air hose, 4 m long, DN 560, Length: 4 m
	235874	<b><u>WPIC 3</u></b>	Air handling module, Height: 637 mm, Width: 1240 mm, Depth: 800 mm
	235199	<b><u>SBPE 400</u></b>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	235950	<b>UP 25/1-8 PCV</b>	Circulation pump
	232805	<b><u>HM Trend</u></b>	Hydraulic module
	233602	<b>WPKI-HK E</b>	Heating circuit assembly without mixing valve
	233603	<b>WPKI-HKM E</b>	Heating circuit assembly with mixing valve
	231890	<b>ZVK-WPL 13/18/23 A SR</b>	Casing, Colour: silver
	232956	<b>AWG 560 H-GL</b>	Grey painted wall transition with weather grille, thermally insulated
	232957	<b>AWG 560 V-GL</b>	Grey painted wall transition with weather grille, thermally insulated
	233837	<b>AWG 560 H-SR</b>	Wall outlet with weather grille, thermally insulated

	233838	<b>AWG 560 V-SR</b>	Wall outlet with weather grille, thermally insulated
	231041	<b>AWG 560 L</b>	Wall outlet for light shaft, thermally insulated
	231044	<b>AWG 600 L</b>	Wall outlet with weather grille, thermally insulated
	003478	<b>Hose connection plate DN 560</b>	Hose connection panel
	185325	<b>KSD 1</b>	Duct silencer, Colour: white
	229286	<b>PK 10</b>	Condensate pump with hose connection, Max. head: 5 m, Max. pump rate: 500 l/h
	185579	<b><u>FE 7</u></b>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	074415	<b>SD 25-1</b>	Pressure hose, angled, with 19 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 80 mm, Connections for the heating and source side: G 1 1/4
	232974	<b>SD 25-1 KE</b>	Pressure hose (can be trimmed), angled, DN 25, 1 m with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	233828	<b>SD 25-2 GE</b>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	232971	<b>SD 25-2.5 GE</b>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2,5 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4

	233711	<b>STB-FB</b>	Safety thermostat, underfloor heating system
	070634	<b>WT 20</b>	Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 136.5 mm
	221360	<b><u>SBB 301 WP</u></b>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221361	<b><u>SBB 302 WP</u></b>	DHW cylinder, Rated capacity: 290 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221362	<b><u>SBB 401 WP SOL</u></b>	DHW cylinder, Rated capacity: 395 l, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	227534	<b><u>SBB 501 WP SOL</u></b>	DHW cylinder, Rated capacity: 495 l, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	233487	<b><u>SBB 300 WP Trend</u></b>	DHW cylinder, Rated capacity: 287 l, Height: 1652 mm, Diameter incl. thermal insulation: 650 mm
	233488	<b><u>SBB 400 WP Trend</u></b>	DHW cylinder, Rated capacity: 390 l, Diameter incl. thermal insulation: 750 mm, Height: 1565 mm
	233489	<b><u>SBB 500 WP Trend</u></b>	DHW cylinder, Rated capacity: 481 l, Height: 1871 mm, Diameter incl. thermal insulation: 750 mm
	185458	<b><u>SBP 200 E</u></b>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	220824	<b><u>SBP 400 E</u></b>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	185459	<b><u>SBP 700 E</u></b>	Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm

	185460	<b><u>SBP 700 E SOL</u></b>	Buffer cylinder, Rated capacity: 703 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	227564	<b><u>SBP 1000 E</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227566	<b><u>SBP 1000 E SOL</u></b>	Buffer cylinder, Rated capacity: 979 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	229980	<b><u>SBS 601 W</u></b>	Instantaneous water cylinder, Rated capacity: 613 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229984	<b><u>SBS 601 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 599 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229981	<b><u>SBS 801 W</u></b>	Instantaneous water cylinder, Rated capacity: 759 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229985	<b><u>SBS 801 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 740 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229982	<b><u>SBS 1001 W</u></b>	Instantaneous water cylinder, Rated capacity: 941 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm
	229986	<b><u>SBS 1001 W SOL</u></b>	Instantaneous water cylinder, Rated capacity: 916 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.