


WPL 13 cool









AIR | WATER HEAT PUMPS









PRODUCT-NO.: 223400












Obligatory supplies

Article	Part no.	Type	Description
	236000	<u>WPM international</u>	Heat pump manager with international operating instructions, Height: 72 mm, Width: 146 mm, Depth: 96 mm





Additional supplies

Article	Part no.	Type	Description
	201619	LSWP 560-4 SG	Sound-optimised air hose, 4 m long, DN 560, grey outer sheath, Length: 4 m
	201620	UP 25/7.5 PCV	Circulation pump, Connection: G 1 1/2
	233010	<u>HM</u>	Hydraulic module
	234763	WPKI 5	Compact installation
	234764	BBI 5	Compact installation
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234349	<u>SBBE 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234350	<u>SBBE 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Depth: 852 mm, Height: 1972 mm, Width: 786 mm

	234351	<u>SBBE 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Height: 1972 mm, Width: 786 mm, Depth: 852 mm
	233510	<u>HSBC 200</u>	Integral cylinder, Nominal capacity, DHW cylinder: 168 l, Nominal capacity, buffer cylinder: 100 l, Depth: 871 mm, Height: 1908 mm, Width: 680 mm
	234647	LSWP 560-4 S	Sound-optimised air hose, 4 m long, DN 560, Length: 4 m
	235874	<u>WPIC 3</u>	Air handling module, Height: 637 mm, Width: 1240 mm, Depth: 800 mm
	235950	UP 25/1-8 PCV	Circulation pump
	236570	<u>SBP 1010 E cool</u>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	232805	<u>HM Trend</u>	Hydraulic module
	233602	WPKI-HK E	Heating circuit assembly without mixing valve
	233603	WPKI-HKM E	Heating circuit assembly with mixing valve
	231890	ZVK-WPL 13/18/23 A SR	Casing, Colour: silver
	232956	AWG 560 H-GL	Grey painted wall transition with weather grille, thermally insulated
	232957	AWG 560 V-GL	Grey painted wall transition with weather grille, thermally insulated
	233837	AWG 560 H-SR	Wall outlet with weather grille, thermally insulated
	233838	AWG 560 V-SR	Wall outlet with weather grille, thermally insulated
	231041	AWG 560 L	Wall outlet for light shaft, thermally insulated

	231044	AWG 600 L	Wall outlet with weather grille, thermally insulated
	003478	Hose connection plate DN 560	Hose connection panel
	185325	KSD 1	Duct silencer, Colour: white
	229286	PK 10	Condensate pump with hose connection, Max. head: 5 m, Max. pump rate: 500 l/h
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	074415	SD 25-1	Pressure hose, angled, with 19 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 80 mm, Connections for the heating and source side: G 1 1/4
	232974	SD 25-1 KE	Pressure hose (can be trimmed), angled, DN 25, 1 m with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	233828	SD 25-2 GE	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	232971	SD 25-2.5 GE	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2,5 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	233711	STB-FB	Safety thermostat, underfloor heating system
	070634	WT 20	Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 136.5 mm

	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221361	<u>SBB 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221362	<u>SBB 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	227534	<u>SBB 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	233487	<u>SBB 300 WP Trend</u>	DHW cylinder, Rated capacity: 287 l, Height: 1652 mm, Diameter incl. thermal insulation: 650 mm
	233488	<u>SBB 400 WP Trend</u>	DHW cylinder, Rated capacity: 390 l, Diameter incl. thermal insulation: 750 mm, Height: 1565 mm
	233489	<u>SBB 500 WP Trend</u>	DHW cylinder, Rated capacity: 481 l, Height: 1871 mm, Diameter incl. thermal insulation: 750 mm
	185460	<u>SBP 700 E SOL</u>	Buffer cylinder, Rated capacity: 703 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	227588	<u>SBP 1000 E cool</u>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227589	<u>SBP 1500 E cool</u>	Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm
	229980	<u>SBS 601 W</u>	Instantaneous water cylinder, Rated capacity: 613 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229984	<u>SBS 601 W SOL</u>	Instantaneous water cylinder, Rated capacity: 599 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm

	229981	<u>SBS 801 W</u>	Instantaneous water cylinder, Rated capacity: 759 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229985	<u>SBS 801 W SOL</u>	Instantaneous water cylinder, Rated capacity: 740 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229982	<u>SBS 1001 W</u>	Instantaneous water cylinder, Rated capacity: 941 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm
	229986	<u>SBS 1001 W SOL</u>	Instantaneous water cylinder, Rated capacity: 916 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.