




WPL 25 AC







AIR | WATER HEAT PUMPS















PRODUCT-NO.: 236645

Obligatory supplies

Article	Part no.	Type	Description
	233622	AS-WP 1	Hydraulic connection set, Connection: 32 x 2.9 mm
	233623	AS-WP 2	Hydraulic connection set, Connection: G 1 1/4
	236000	<u>WPM international</u>	Heat pump manager with international operating instructions, Height: 72 mm, Width: 146 mm, Depth: 96 mm

Additional supplies

Article	Part no.	Type	Description
	232964	SK 1	T-support with 1 m long ribbon heater
	200168	<u>FEK 2</u>	Remote control with room temperature and humidity sensors, Height: 97,00 mm, Width: 147,00 mm, Depth: 33 mm
	201620	UP 25/7.5 PCV	Circulation pump, Connection: G 1 1/2
	235950	UP 25/1-8 PCV	Circulation pump
	233010	<u>HM</u>	Hydraulic module
	232978	HZB-1	Ribbon heater 1 m, Rated voltage: 230 V, Power supply: 1/N/PE

	232979	HZB-2	Ribbon heater 2 m, Rated voltage: 230 V, Power supply: 1/N/PE
	232805	<u>HM Trend</u>	Hydraulic module
	234763	WPKI 5	Compact installation
	234764	BBI 5	Compact installation
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	233510	<u>HSBC 200</u>	Integral cylinder, Nominal capacity, DHW cylinder: 168 l, Nominal capacity, buffer cylinder: 100 l, Depth: 871 mm, Height: 1908 mm, Width: 680 mm
	234722	WK 2	Wall mounting panel
	233602	WPKI-HK E	Heating circuit assembly without mixing valve
	233603	WPKI-HKM E	Heating circuit assembly with mixing valve
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	233711	STB-FB	Safety thermostat, underfloor heating system
	233831	SD 32-2 GE	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 32, Length: 2 m, External diameter with insulation: 106 mm, Connections for the heating and source side: G 1 1/4
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm



233487

SBB 300 WP Trend

DHW cylinder, Rated capacity: 287 l, Height:
1652 mm, Diameter incl. thermal insulation:
650 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.