


# WPL 33









AIR | WATER HEAT PUMPS





PRODUCT-NO.: 185348

## Obligatory supplies

| Article   | Part no. | Type                        | Description   |
|---|----------|-----------------------------|---|
|  | 234922   | <b>WPMW 3 international</b> | Heat pump manager, Height: 215 mm, Width: 246 mm, Depth: 140 mm |

## Additional supplies

| Article   | Part no. | Type                          | Description  |
|---|----------|-------------------------------|--|
|  | 234763   | <b>WPKI 5</b>                 | Compact installation   |
|  | 234764   | <b>BBI 5</b>                  | Compact installation   |
|  | 234351   | <b><u>SBBE 501 WP SOL</u></b> | DHW cylinder, Rated capacity: 495 l, Height: 1972 mm, Width: 786 mm, Depth: 852 mm                   |
|  | 234647   | <b>LSWP 560-4 S</b>           | Sound-optimised air hose, 4 m long, DN 560, Length: 4 m  |
|  | 234921   | <b>WPMS 3 international</b>   | Heat pump manager, Height: 72 mm, Width: 146 mm, Depth: 96 mm  |
|  | 235949   | <b>UP 25/7.5 PCV</b>          | Circulation pump   |
|  | 235950   | <b>UP 25/1-8 PCV</b>          | Circulation pump   |
|  | 236569   | <b><u>SBP 1010 E</u></b>      | Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm |

|   |        |                                     |  |
|---|--------|-------------------------------------|--|
|    | 236570 | <b><u>SBP 1010 E cool</u></b>       | Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm |
|    | 232956 | <b>AWG 560 H-GL</b>                 | Grey painted wall transition with weather grille, thermally insulated                                |
|    | 232957 | <b>AWG 560 V-GL</b>                 | Grey painted wall transition with weather grille, thermally insulated                                |
|    | 233837 | <b>AWG 560 H-SR</b>                 | Wall outlet with weather grille, thermally insulated   |
|    | 233838 | <b>AWG 560 V-SR</b>                 | Wall outlet with weather grille, thermally insulated   |
|    | 231041 | <b>AWG 560 L</b>                    | Wall outlet for light shaft, thermally insulated   |
|  | 231044 | <b>AWG 600 L</b>                    | Wall outlet with weather grille, thermally insulated   |
|   | 185368 | <b>ZVK-WPL 33 I</b>                 | Casing, Colour: white  |
|   | 185369 | <b>ZVK-WPL 33 A</b>                 | Casing, Colour: white  |
|  | 003478 | <b>Hose connection plate DN 560</b> | Hose connection panel  |
|  | 185370 | <b>KSD 2</b>                        | Duct silencer, Colour: white   |
|  | 229286 | <b>PK 10</b>                        | Condensate pump with hose connection, Max. head: 5 m, Max. pump rate: 500 l/h                        |
|  | 233602 | <b>WPKI-HK E</b>                    | Heating circuit assembly without mixing valve  |
|  | 233603 | <b>WPKI-HKM E</b>                   | Heating circuit assembly with mixing valve   |
|  | 227956 | <b>AUK 14</b>                       | Fan convactor heater, Heating output, medium: 1,4 kW, Height: 600 mm, Depth: 142 mm, Width: 890 mm   |

|   |        |                                |  |
|---|--------|--------------------------------|--|
|    | 227957 | <b>AUK 21</b>                  | Fan convector heater, Heating output, medium: 1,75 kW, Height: 600 mm, Depth: 142 mm, Width: 1090 mm |
|    | 227958 | <b>AUK 28</b>                  | Fan convector heater, Heating output, medium: 2,1 kW, Height: 600 mm, Depth: 142 mm, Width: 1290 mm  |
|    | 227959 | <b>AUK 35</b>                  | Fan convector heater, Heating output, medium: 2,35 kW, Height: 600 mm, Depth: 142 mm, Width: 1490 mm |
|    | 227955 | <b>AUK 7</b>                   | Fan convector heater, Heating output, medium: 0,65 kW, Height: 600 mm, Depth: 142 mm, Width: 690 mm  |
|    | 071091 | <b>WT 30</b>                   | Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 173.5 mm                                       |
|  | 229293 | <b><u>SBB 1001</u></b>         | DHW cylinder, Rated capacity: 1004 l, Height: 2277 mm, Diameter incl. thermal insulation: 1010 mm    |
|  | 229295 | <b><u>SBB 1001 SOL</u></b>     | DHW cylinder, Rated capacity: 971 l, Height: 2277 mm, Diameter incl. thermal insulation: 1010 mm     |
|  | 227534 | <b><u>SBB 501 WP SOL</u></b>   | DHW cylinder, Rated capacity: 495 l, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm      |
|  | 233489 | <b><u>SBB 500 WP Trend</u></b> | DHW cylinder, Rated capacity: 481 l, Height: 1871 mm, Diameter incl. thermal insulation: 750 mm      |
|  | 227564 | <b><u>SBP 1000 E</u></b>       | Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm |
|  | 227588 | <b><u>SBP 1000 E cool</u></b>  | Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm |

|   |        |                               |   |
|---|--------|-------------------------------|---|
|    | 227566 | <b><u>SBP 1000 E SOL</u></b>  | Buffer cylinder, Rated capacity: 979 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm               |
|    | 227565 | <b><u>SBP 1500 E</u></b>      | Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm              |
|    | 227589 | <b><u>SBP 1500 E cool</u></b> | Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm              |
|    | 227567 | <b><u>SBP 1500 E SOL</u></b>  | Buffer cylinder, Rated capacity: 1473 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm              |
|   | 185459 | <b><u>SBP 700 E</u></b>       | Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm                |
|  | 185460 | <b><u>SBP 700 E SOL</u></b>   | Buffer cylinder, Rated capacity: 703 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm                |
|  | 229982 | <b><u>SBS 1001 W</u></b>      | Instantaneous water cylinder, Rated capacity: 941 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm  |
|  | 229986 | <b><u>SBS 1001 W SOL</u></b>  | Instantaneous water cylinder, Rated capacity: 916 l, Height: 2240 mm, Diameter incl. thermal insulation: 1010 mm  |
|  | 229983 | <b><u>SBS 1501 W</u></b>      | Instantaneous water cylinder, Rated capacity: 1430 l, Height: 2155 mm, Diameter incl. thermal insulation: 1220 mm |
|  | 229987 | <b><u>SBS 1501 W SOL</u></b>  | Instantaneous water cylinder, Rated capacity: 1399 l, Height: 2155 mm, Diameter incl. thermal insulation: 1220 mm |

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.