


WPC 07









BRINE-WATER HEAT PUMPS











PRODUCT-NO.: 232928

Obligatory supplies

Article	Part no.	Type	Description
	233307	<u>WPSE</u>	Brine filling unit

Additional supplies

Article	Part no.	Type	Description
	235233	<u>MFS-WP 22</u>	Pressure gauge filter set, Connection: G 1 A / Cu 22 x 1
	221382	DWS1	Brine pressure switch
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	233602	<u>WPKI-HK E</u>	Heating circuit assembly without mixing valve
	233511	<u>FS-WP 22</u>	Filter assembly, Connection: G 1 A / Cu 22 x 1
	233512	<u>FS-WP 28</u>	Filter assembly, Connection: G 1 1/4 A / Cu 28 x 1.5
	235199	<u>SBPE 400</u>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	233603	<u>WPKI-HKM E</u>	Heating circuit assembly with mixing valve

	185459	<u>SBP 700 E</u>	Buffer cylinder, Rated capacity: 720 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	161696	<u>MEG 30</u>	Heat transfer medium, 30 litres, Liquid content: 30 l
	232461	<u>WPSV 25-6</u>	Brine distributor DN 20, Number of brine circuits: 6, Ball valve with clamp fitting: DN 20
	220824	<u>SBP 400 E</u>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	233711	<u>STB-FB</u>	Safety thermostat, underfloor heating system
	235234	<u>MFS-WP 28</u>	Pressure gauge filter set, Connection: G 1 1/4 A / Cu 28 x 1.5
	235218	<u>MAG 12</u>	Brine expansion vessel, Expansion vessel: 12 l, Inlet pressure: 0,05 MPa
	234762	<u>WPKI 6</u>	Compact installation
	221135	<u>WPHW 25</u>	Low loss header, Heat pump connection: G 1 1/2, Heating connection: G 1 1/2, Flow rate: 2 m ³ /h

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.