


# WPC 05 S










BRINE-WATER HEAT PUMPS









PRODUCT-NO.: 232937

## Obligatory supplies

Article	Part no.	Type	Description
	233307	<b><u>WPSE</u></b>	Brine filling unit

## Additional supplies

Article	Part no.	Type	Description
	235199	<b><u>SBPE 400</u></b>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	235233	<b><u>MFS-WP 22</u></b>	Pressure gauge filter set, Connection: G 1 A / Cu 22 x 1
	233511	<b><u>FS-WP 22</u></b>	Filter assembly, Connection: G 1 A / Cu 22 x 1
	232461	<b>WPSV 25-6</b>	Brine distributor DN 20, Number of brine circuits: 6, Ball valve with clamp fitting: DN 20
	233512	<b><u>FS-WP 28</u></b>	Filter assembly, Connection: G 1 1/4 A / Cu 28 x 1.5
	234762	<b><u>WPKI 6</u></b>	Compact installation
	233602	<b><u>WPKI-HK E</u></b>	Heating circuit assembly without mixing valve
	221382	<b>DWS1</b>	Brine pressure switch
	235218	<b><u>MAG 12</u></b>	Brine expansion vessel, Expansion vessel: 12 l, Inlet pressure: 0,05 MPa

	233711	<b>STB-FB</b>	Safety thermostat, underfloor heating system
	233603	<b><u>WPKI-HKM E</u></b>	Heating circuit assembly with mixing valve
	161696	<b><u>MEG 30</u></b>	Heat transfer medium, 30 litres, Liquid content: 30 l
	221135	<b><u>WPHW 25</u></b>	Low loss header, Heat pump connection: G 1 1/2, Heating connection: G 1 1/2, Flow rate: 2 m <sup>3</sup> /h
	185459	<b><u>SBP 700 E</u></b>	Buffer cylinder, Rated capacity: 720 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	220824	<b><u>SBP 400 E</u></b>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	235234	<b><u>MFS-WP 28</u></b>	Pressure gauge filter set, Connection: G 1 1/4 A / Cu 28 x 1.5
	185458	<b><u>SBP 200 E</u></b>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.