

HPG-I 12 S Premium

GROUND SOURCE HEAT PUMPS

PRODUCT-NO.: 202620

Open your door to comfortable living

Boost your home comforts with this ground source heat pump. The appliance with inverter technology draws heat from the ground for your central heating and domestic hot water. We also offer a version that provides passive cooling for your house as and when required. In both summer and winter, this ingenious piece of engineering elevates your living comfort to new levels, thanks to its consistent heating output with high flow temperatures.



Make the most of this all-rounder

One of our five output sizes will be just right for you, whether it's for a new building or a modernisation project. The inverter technology guarantees you the exact heating output you want at any given time. This reduces your energy consumption to a minimum, saves you money and even optimises your room climate – all at the same time.



HPG-I 04 S Premium

Product-No.: 202617



HPG-I 06 S Premium

Product-No.: 202618



HPG-I 08 S Premium

Product-No.: 202619



HPG-I 15 S Premium

Product-No.: 202621

The main features

Ground source heat pump installed indoors for heating, with cooling as an optional extra

Optimum output and maximum efficiency thanks to inverter technology

Futureproof and eco-friendly refrigerant

Optional integration into the home network and control via smartphone

Flow temperatures of up to 75 °C for energy efficient heating and high mixed water volumes



Type	HPG-I 04 S Premium	HPG-I 06 S Premium	HPG-I 08 S Premium
Part no.	202617	202618	202619

Technical data

Energy efficiency class, heat pump W35	A+++	A+++	A+++
Energy efficiency class, heat pump W55	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+++	A+++	A+++
Heating output at B0/W35 (EN 14511)	1,96 kW	2,37 kW	2,78 kW
Heating output at B0/W35 (min./max.)	1,0-4,2 kW	1,0 - 6,6 kW	1,0-7,6 kW
COP at B0/W35 (EN 14511)	4.60	4.60	4.67
SCOP 35 °C (EN 14825)	5.07	5.20	5.12
Sound power level (EN 12102)	38-40 dB(A)	38-43 dB(A)	38-45 dB(A)
Max. application limit on the heating side	75 °C	75 °C	75 °C
Height	1369 mm	1369 mm	1369 mm
Width	598 mm	598 mm	598 mm
Depth	658 mm	658 mm	658 mm
Weight	180 kg	180 kg	180 kg
Rated voltage, compressor	230 V	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V	230 V
Refrigerant	R454C	R454C	R454C
Connection, heating side	28 mm	28 mm	28 mm
Connection, heat source side	28 mm plug-in connection	28 mm plug-in connection	28 mm plug-in connection



Type	HPG-I 12 S Premium	HPG-I 15 S Premium
Part no.	202620	202621

Technical data

Energy efficiency class, heat pump W35	A+++	A+++
Energy efficiency class, heat pump W55	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W35	A+++	A+++
Energy efficiency class, composite system (heat pump + controller) W55	A+++	A+++
Heating output at B0/W35 (EN 14511)	4,19 kW	5,18 kW
Heating output at B0/W35 (min./max.)	2,1-12,7 kW	2,1 - 14,8 kW
COP at B0/W35 (EN 14511)	5.01	4.86
SCOP 35 °C (EN 14825)	5.59	5.44
Sound power level (EN 12102)	39-46 dB(A)	39-47 dB(A)
Max. application limit on the heating side	75 °C	75 °C
Height	1369 mm	1369 mm
Width	598 mm	598 mm
Depth	658 mm	658 mm
Weight	190 kg	190 kg
Rated voltage, compressor	230 V	230 V
Rated voltage, emergency/auxiliary heater	230 V	230 V
Refrigerant	R454C	R454C
Connection, heating side	28 mm	28 mm
Connection, heat source side	28 mm plug-in connection	28 mm plug-in connection

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.