

WPF 16 M

PRODUCT-NO.: 220894

A solution that lives up to your expectations

This ingenious universal appliance grows with your needs. It is small enough to do reliable service in your family home. And it is sufficiently powerful to offer you a substantial heating output in buildings with a high energy demand as well.

Double the benefit with a practical duo

If you're after something practical for your commercial building, we recommend the WPF Set. It comes with all the necessary components such as controllers and hydraulics. The set comprises two heat pumps in a cascade.



The main features

Ground source heat pump installed indoors for heating

Suitable for new build and modernisation projects

Can be installed almost anywhere with three output sizes and cascade connection

Pleasantly quiet operation

Suitable for standard radiators with flow temperatures of up to 60°C



Type	WPF 10 M	WPF 13 M	WPF 16 M
Part no.	185349	182135	220894

Technical data

Heating output at B0/W35 (EN 14511)	10.02 kW	12.98 kW	16.99 kW
COP at B0/W35 (EN 14511)	4.49	4.57	4.35
SCOP (EN 14825)	5.075	5.125	4.875
Sound power level (EN 12102)	51 dB(A)	53 dB(A)	53 dB(A)
Max. application limit on the heating side	60 °C	60 °C	60 °C
Height	960 mm	960 mm	960 mm
Width	510 mm	510 mm	510 mm
Depth	680 mm	680 mm	680 mm
Weight	112 kg	120 kg	125 kg
Rated voltage, compressor	400 V	400 V	400 V
Refrigerant	R410A	R410A	R410A

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.