

























WPF 7 MS

BRINE | WATER HEAT PUMPS

PRODUCT-NO.: 222553

Additional supplies

Article	Part no.	Type	Description
	234763	WPKI 5	Compact installation
	234348	SBBE 301 WP	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234349	SBBE 302 WP	DHW cylinder, Rated capacity: 290 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234921	WPMS 3 international	Heat pump manager, Height: 72 mm, Width: 146 mm, Depth: 96 mm
	235199	SBPE 400	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	235949	UP 25/7.5 PCV	Circulation pump
	235950	UP 25/1-8 PCV	Circulation pump
	161696	MEG 30	Heat transfer medium, 30 litres, Liquid content: 30 l
	233602	WPKI-HK E	Heating circuit assembly without mixing valve
	233603	WPKI-HKM E	Heating circuit assembly with mixing valve
	233098	WPKI-H E	Heating circuit assembly without mixing valve
	233097	WPKI-P E	Compact installation

	233099	WPKI-W E	Compact installation
	233711	STB-FB	Safety thermostat, underfloor heating system
	230381	WPM-RBS	Relay set for high efficiency pumps, Height: 211 mm, Width: 205 mm, Depth: 56 mm
	222375	WPSB 308 E	Brine assembly for the heat source system including high efficiency pump
	232461	WPSV 25-6	Brine distributor DN 20, Number of brine circuits: 6, Ball valve with clamp fitting: DN 20
	185458	SBP 200 E	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	220824	SBP 400 E	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	185459	SBP 700 E	Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm
	185460	SBP 700 E SOL	Buffer cylinder, Rated capacity: 703 l, Height: 1890 mm, Diameter incl. thermal insulation: 910 mm
	221360	SBB 301 WP	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221361	SBB 302 WP	DHW cylinder, Rated capacity: 290 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	233488	SBB 400 WP Trend	DHW cylinder, Rated capacity: 390 l, Diameter incl. thermal insulation: 750 mm, Height: 1565 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.