


# WPF 52









BRINE | WATER HEAT PUMPS









PRODUCT-NO.: 233007

## Obligatory supplies

Article	Part no.	Type	Description
	236000	<b><u>WPM international</u></b>	Heat pump manager with international operating instructions, Height: 400 mm, Width: 310 mm, Depth: 100 mm

## Additional supplies

Article	Part no.	Type	Description
	236569	<b><u>SBP 1010 E</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	236570	<b><u>SBP 1010 E cool</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	161696	<b>MEG 30</b>	Heat transfer medium, 30 litres, Liquid content: 30 l
	227422	<b>UP 40/1-8 E</b>	Circulation pump
	227413	<b>UPF 40/1-8 E</b>	Brine circuit pump
	227423	<b>UP 50/1-12 E</b>	Circulation pump
	227414	<b>UPF 50/1-12 E</b>	Brine circuit pump
	185579	<b><u>FE 7</u></b>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm

	232462	<b>WPSV 32-4</b>	Brine distributor DN 25, Number of brine circuits: 4, Ball valve with clamp fitting: DN 25
	003711	<b>Connection Components SBP</b>	Inserts
	232908	<b>WTS 40 E</b>	Loading station, DHW heating, Height: 1090 mm, Width: 520 mm, Depth: 305 mm
	185459	<b><u>SBP 700 E</u></b>	Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm
	227564	<b><u>SBP 1000 E</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227588	<b><u>SBP 1000 E cool</u></b>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227565	<b><u>SBP 1500 E</u></b>	Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm
	227589	<b><u>SBP 1500 E cool</u></b>	Buffer cylinder, Rated capacity: 1503 l, Height: 2220 mm, Diameter incl. thermal insulation: 1220 mm

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.