

























WPF 16 basic

BRINE | WATER HEAT PUMPS

PRODUCT-NO.: 230948

Additional supplies

Article	Part no.	Type	Description
	161696	MEG 30	Heat transfer medium, 30 litres, Liquid content: 30 l
	230660	<u>GWS 2</u>	Groundwater module, Height: 630 mm, Width: 640 mm, Depth: 230 mm, Weight: 26,50 kg
	234762	WPKI 6	Compact installation
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234349	<u>SBBE 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234350	<u>SBBE 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Depth: 852 mm, Height: 1972 mm, Width: 786 mm
	234351	<u>SBBE 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Height: 1972 mm, Width: 786 mm, Depth: 852 mm
	235199	<u>SBPE 400</u>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	201620	UP 25/7.5 PCV	Circulation pump, Connection: G 1 1/2
	233602	WPKI-HK E	Heating circuit assembly without mixing valve
	233603	WPKI-HKM E	Heating circuit assembly with mixing valve
	074347	WPKI-V	Compact installation

	232965	SD 25-1 E	Pressure hose, angled, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	232968	SD 32-1 E	Pressure hose, angled, with 30 mm thermal insulation, For pressure hose size DN: 32, Length: 1 m, External diameter with insulation: 106 mm, Connections for the heating and source side: G 1 1/4
	074415	SD 25-1	Pressure hose, angled, with 19 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 80 mm, Connections for the heating and source side: G 1 1/4
	233711	STB-FB	Safety thermostat, underfloor heating system
	232883	WPSB 312 E	Brine assembly for the heat source system including high efficiency pump
	232460	WPSV 25-4	Brine distributor DN 20, Number of brine circuits: 4, Ball valve with clamp fitting: DN 20
	230381	<u>WPM-RBS</u>	Relay set for high efficiency pumps, Height: 211 mm, Width: 205 mm, Depth: 56 mm
	221135	WPHW 25	Low loss header, Heat pump connection: G 1 1/2, Heating connection: G 1 1/2, Flow rate: 2 m ³ /h
	221382	DWS1	Brine pressure switch
	230659	<u>GWS 1</u>	Groundwater module, Height: 630 mm, Width: 640 mm, Depth: 230 mm, Weight: 20,50 kg
	227420	HUV 1	Heating diverter valve, Connection: G1
	070633	WT 10	Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 99.6 mm

	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221361	<u>SBB 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221362	<u>SBB 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	227534	<u>SBB 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Height: 1988 mm, Diameter incl. thermal insulation: 810 mm
	233487	<u>SBB 300 WP Trend</u>	DHW cylinder, Rated capacity: 287 l, Height: 1652 mm, Diameter incl. thermal insulation: 650 mm
	233488	<u>SBB 400 WP Trend</u>	DHW cylinder, Rated capacity: 390 l, Diameter incl. thermal insulation: 750 mm, Height: 1565 mm
	233489	<u>SBB 500 WP Trend</u>	DHW cylinder, Rated capacity: 481 l, Height: 1871 mm, Diameter incl. thermal insulation: 750 mm
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	220824	<u>SBP 400 E</u>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	185459	<u>SBP 700 E</u>	Buffer cylinder, Rated capacity: 720 l, Diameter incl. thermal insulation: 910 mm, Height: 1890 mm
	229980	<u>SBS 601 W</u>	Instantaneous water cylinder, Rated capacity: 613 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229984	<u>SBS 601 W SOL</u>	Instantaneous water cylinder, Rated capacity: 599 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm



229981

SBS 801 W

Instantaneous water cylinder, Rated capacity:
759 l, Height: 1830 mm, Diameter incl. thermal
insulation: 1010 mm



229985

SBS 801 W SOL

Instantaneous water cylinder, Rated capacity:
740 l, Height: 1830 mm, Diameter incl. thermal
insulation: 1010 mm

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.