







WWK 301 electronic

DHW HEAT PUMPS

PRODUCT-NO.: 230950

Additional supplies

Article	Part no.	Type	Description
	236899	LUS 221/301	Air diverter hood set, Connection: DN 160
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 3/4 A
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.
	074374	SV 3/4-6	Diaphragm safety valve with brass casing, response pressure 0.6 Mpa (6 bar).
	073864	ZTA 3/4	Thermostatic valve, Water connection: G 3/4 A
	234505	AWG 160 R	Thermally insulating EPS wall outlet incl. weather grille with drip edge, Max. air flow rate: 350 m ³ /h, External pipe diameter: 200 mm, Connection diameter: 160 mm, Max. air volume: 350 m ³ /h

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.