















SOL 23 premium

SOLAR COLLECTORS

PRODUCT-NO.: 230020

Additional supplies

Article	Part no.	Type	Description
	073221	H-30 L, 10 litres	Heat transfer medium, Content: 10 l, Colour: blue, Resistant to constant temperatures up to: 150 °C
	073222	H-30 L, 20 litres	Heat transfer medium, Content: 20 l, Colour: blue, Resistant to constant temperatures up to: 150 °C
	074029	AG 12	Diaphragm expansion vessel, suitable for H-30 L, Volume: 12 l, Connection: G 1/2
	074030	AG 18	Diaphragm expansion vessel, suitable for H-30 L, Volume: 18 l, Connection: G 3/4
	074031	AG 25	Diaphragm expansion vessel, suitable for H-30 L, Volume: 25 l, Connection: G 3/4
	074099	H-30 LS, 10 litres	Heat transfer medium, Content: 10 l, Colour: Red, fluorescent, Resistant to constant temperatures up to: 170 °C
	074100	H-30 LS, 20 litres	Heat transfer medium, Content: 20 l, Colour: Red, fluorescent, Resistant to constant temperatures up to: 170 °C
	187868	AG 50	Diaphragm expansion vessel, suitable for H-30 L, Volume: 50 l, Connection: G 3/4
	187873	<u>SBB 300 plus</u>	Solar DHW cylinder, Rated capacity: 305 l, Diameter incl. thermal insulation: 700 mm, Height: 1679 mm
	187874	<u>SBB 400 plus</u>	Solar DHW cylinder, Rated capacity: 416 l, Diameter incl. thermal insulation: 750 mm, Height: 1848 mm

	187875	<u>SBB 600 plus</u>	Solar DHW cylinder, Rated capacity: 611 l, Diameter incl. thermal insulation: 920 mm, Height: 1735 mm
	230184	<u>SOL AS</u>	Side flashing set
	231899	AG 80	Diaphragm expansion vessel (type-tested), H-30 L, Volume: 80 l, Connection: G1
	232944	SFR 10	Flexible solar pipe DN 20, 10 m long
	232945	SFR 15	Flexible solar pipe DN 20, 15 m long
	232946	SFR 20	Flexible solar pipe DN 20, 20 m long
	232947	SFR 25	Flexible solar pipe DN 20, 25 m long
	233490	<u>SBB 300 Trend</u>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 650 mm, Height: 1652 mm
	233491	<u>SBB 400 Trend</u>	Solar DHW cylinder, Rated capacity: 404 l, Diameter incl. thermal insulation: 750 mm, Height: 1566 mm
	233492	<u>SBB 500 Trend</u>	Solar DHW cylinder, Rated capacity: 498 l, Diameter incl. thermal insulation: 750 mm, Height: 1871 mm
	234783	<u>SOKI E Trend</u>	Solar compact installation
	230187	<u>SOL SV-I</u>	Collector plug-in connection
	230188	<u>SOL SV-R</u>	Plug-in connection, collector array
	230183	<u>SOL AZ</u>	Cover, extension, stacked



073469

**Corrugated stainless
steel hose**

Corrugated stainless steel hose

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.