

RBS 301

ACCESSORIES

PRODUCT-NO.: 234515

RBS pipe assembly, thermally insulated, for use with floorstanding DHW cylinders SBBE 301 - 501 WP SOL. Available as a set for easy optional relocation of the hydraulic connections of the indirect coils and the DHW connections to the top, behind the cylinder. From there, the on-site connections are made to the copper connectors. One drain valve is included in each of the return connections of the indirect coils. Pipes are run through an installation rail on the cylinder to align the individual pre-assembled connection pipework.



The main features

Optional upward relocation of hydraulic cylinder connections, behind the cylinder

Straightforward connection technology on the cylinder using union nuts and copper connectors on site

RBS 401.2 and RBS 501.2 must be used when connecting both indirect coils in series



Type	RBS 401.2	RBS 501.2	RBS 301
Part no.	234512	234514	234515

Technical data

Heat pump connection	28 mm	28 mm	28 mm
Solar connection	22 mm	22 mm	22 mm
Cold water connection	22 mm	22 mm	22 mm
DHW connection	22 mm	22 mm	22 mm
DHW circulation connection	15 mm	15 mm	15 mm



Type	RBS 302
------	---------

Part no.	234516
----------	--------

Technical data

Heat pump connection	28 mm
----------------------	-------

Solar connection	22 mm
------------------	-------

Cold water connection	22 mm
-----------------------	-------

DHW connection	22 mm
----------------	-------

DHW circulation connection	15 mm
----------------------------	-------

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.