

WDH 1000 cool

PRODUCT-NO.: 231921

High grade EPTS rigid foam thermal insulation with insulated cover and floor disc for SBP 1000 to 1500 buffer cylinders. Graphite inserts in the EPTS and fleece for lowest heat losses. Wedge-shaped cut-outs and fleece layer ensure an optimum fit around the cylinder. Prepared adhesive joint in the wedge-shaped cut-outs enables adjustment to the shape prior to installation. External plastic jacket in white; cover in basalt grey. Thermal insulation secured with a quick-release hook strip.



The main features

Composite thermal insulation made from rigid foam and fleece

Graphite inserts for good insulation properties

Two insulation semi-shells to make it easier to match the shape

A pre-insulated cylinder can be used for cooling in conjunction with this thermal insulation



Type	WDH 1000 cool	WDH 1500 cool
Part no.	231921	231922

Technical data

Insulation for	SBP 1000 E cool and SBP 1010 E cool	SBP 1500 E cool
Thermal insulation thickness	110 mm	110 mm
Standby energy consumption/ 24 h at 65 °C	3.50 kWh	4.00 kWh

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.