

SB-VTS 400/3

DHW CYLINDER

PRODUCT-NO.: 200164

The main features

Enamelled cylinder interior for solar thermal DHW heating

Protective anode as standard

Insulated with directly applied foam in the form of a sheet metal jacket





Type	SB-VTS 200/3	SB-VTS 300/3	SB-VTS 400/3
Part no.	200162	200163	200164
Rated capacity	191 l	291 l	407 l
Diameter incl. thermal insulation	550 mm	650 mm	750 mm
Height	1574 mm	1552 mm	1543 mm

Technical data

Energy efficiency class	C	C	C
Standby energy consumption/24 h at 65 °C	1,5 kWh	2,2 kWh	2,5 kWh
Surface, indirect coil, top	0,6 m ²	0,6 m ²	0,7 m ²
Surface area, lower indirect coil	0,9 m ²	1,5 m ²	1,9 m ²
Flanged aperture	180 mm	180 mm	180 mm
Height of unit when tilted	1700 mm	1730 mm	1700 mm
Max. recommended collector aperture area	4 m ²	6 m ²	10 m ²
Weight	98 kg	130 kg	195 kg



Type	SB-VTS 500/3
Part no.	200165
Rated capacity	488 l
Diameter incl. thermal insulation	750 mm
Height	1813 mm

Technical data

Energy efficiency class	C
Standby energy consumption/24 h at 65 °C	2,7 kWh
Surface, indirect coil, top	1 m ²
Surface area, lower indirect coil	2,3 m ²
Flanged aperture	180 mm
Height of unit when tilted	1970 mm
Max. recommended collector aperture area	12 m ²
Weight	225 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.