











SBB 302 WP

DHW CYLINDER

PRODUCT-NO.: 221361

Additional supplies

Article	Part no.	Type	Description
	075115	BGC/45	Threaded immersion heater, Depth of insertion: 455 mm
	232030	BGC 2/60	Threaded immersion heater, Depth of insertion: 480 mm
	233719	UPZ	DHW circulation pump, Connection: G 1/2
	071330	FCR 21/60	Flanged immersion heater, Connected load with ~ 230 V: 2-4 kW, Connected load with ~ 400 V: 2-6 kW, Version: Single/two line
	071331	FCR 21/120	Flanged immersion heater, Connected load with ~ 230 V: 4 kW, Connected load with ~ 400 V: 8/12 kW, Version: Single circuit
	076062	WTW 21/13	Flange diameter: 210 mm
	072119	WTFS 21/13	Flange diameter: 210 mm
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 3/4 A
	074375	SV 3/4-10	Safety valve
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the

installation location exceeds 0.48 MPa (4.8 bar).
Brass. Connection 3/4 inch.

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.