

SBB 800 WP SOL

DHW CYLINDER

PRODUCT-NO.: 235907

Additional supplies

Article	Part no.	Type	Description
	235910	WDH 800 SBB	Thermal insulation, Standby energy consumption/24 h at 65 °C: 3,0 kWh, Insulation for: SBB 800 WP SOL, Height: 2065 mm, Thickness: 110 mm
	000694	FCR 28/120	Flanged immersion heater, Connected load with ~ 400 V: 12 kW, Version: Single circuit
	000695	FCR 28/180	Flanged immersion heater, Connected load with ~ 400 V: 18 kW, Version: Single circuit
	000696	FCR 28/270	Flanged immersion heater, Connected load with ~ 400 V: 27 kW, Version: Single circuit
	001502	FCR 28/360	Flanged immersion heater, Connected load with ~ 400 V: 36 kW, Version: Single circuit
	232629	WRV 40	Corrugated pipe connector, heat exchanger, Internal diameter, corrugated pipe: DN 40
	075124	FCR 28/360 Si	Flanged immersion heater, Connected load with ~ 400 V: 36 kW, Version: Single circuit
	075131	FCR 28/180 Si	Flanged immersion heater, Connected load with ~ 400 V: 18 kW, Version: Single circuit
	075140	FCR 28/120 Si	Flanged immersion heater, Connected load with ~ 400 V: 12 kW, Version: Single circuit
	075141	FCR 28/270 Si	Flanged immersion heater, Connected load with ~ 400 V: 27 kW, Version: Single circuit



233719

UPZ

DHW circulation pump, Connection: G 1/2

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.