


SBB 751








DHW CYLINDER










PRODUCT-NO.: 229292

Obligatory supplies

Article	Part no.	Type	Description
	231923	<u>WDH 751 SBB</u>	Thermal insulation, Standby energy consumption/24 h at 65 °C: 2,9 kWh, Insulation for: SBB 751 and 751 SOL, Height: 1840 mm, Thickness: 110 mm

Additional supplies

Article	Part no.	Type	Description
	071333	FCR 28/180	Flanged immersion heater, Connected load with ~ 400 V: 9/18 kW, Version: Single/two line
	075124	FCR 28/360 Si	Flanged immersion heater, Connected load with ~ 400 V: 36 kW, Version: Single circuit
	232030	BGC 2/60	Threaded immersion heater, Depth of insertion: 480 mm
	000694	FCR 28/120	Flanged immersion heater, Connected load with ~ 400 V: 12 kW, Version: Single circuit
	232907	<u>WTS 30 E</u>	Loading station, DHW heating, Height: 860 mm, Width: 500 mm, Depth: 290 mm
	234503	FCR 28/120 CrNi	Flanged immersion heater, Connected load with ~ 400 V: 6/12 kW, Version: Single/two line
	001502	FCR 28/360	Flanged immersion heater, Connected load with ~ 400 V: 36 kW, Version: Single circuit
	233719	<u>UPZ</u>	DHW circulation pump, Connection: G 1/2

	075140	FCR 28/120 Si	Flanged immersion heater, Connected load with ~ 400 V: 12 kW, Version: Single circuit
	075141	FCR 28/270 Si	Flanged immersion heater, Connected load with ~ 400 V: 27 kW, Version: Single circuit
	231923	<u>WDH 751 SBB</u>	Thermal insulation, Standby energy consumption/24 h at 65 °C: 2,9 kWh, Insulation for: SBB 751 and 751 SOL, Height: 1840 mm, Thickness: 110 mm
	075131	FCR 28/180 Si	Flanged immersion heater, Connected load with ~ 400 V: 18 kW, Version: Single circuit
	232908	<u>WTS 40 E</u>	Loading station, DHW heating, Height: 1090 mm, Width: 520 mm, Depth: 305 mm
	000696	FCR 28/270	Flanged immersion heater, Connected load with ~ 400 V: 27 kW, Version: Single circuit
	000695	FCR 28/180	Flanged immersion heater, Connected load with ~ 400 V: 18 kW, Version: Single circuit
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.
	074375	SV 3/4-10	Safety valve
	071332	FCR 28/120	Flanged immersion heater, Connected load with ~ 400 V: 6/12 kW, Version: Single/two line
	074370	ZH 1	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,60 MPa, Connection: G 1 A

Contact information

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.