









# SBBE 301 WP

DHW CYLINDER

PRODUCT-NO.: 234348

## Additional supplies

Article	Part no.	Type	Description
	071330	<b>FCR 21/60</b>	Flanged immersion heater, Connected load with ~ 230 V: 2-4 kW, Connected load with ~ 400 V: 2-6 kW, Version: Single/two line
	071331	<b>FCR 21/120</b>	Flanged immersion heater, Connected load with ~ 230 V: 4 kW, Connected load with ~ 400 V: 8/12 kW, Version: Single circuit
	074375	<b>SV 3/4-10</b>	Safety valve
	075115	<b>BGC/45</b>	Threaded immersion heater, Depth of insertion: 455 mm
	234515	<b><u>RBS 301</u></b>	Pipe assembly
	233719	<b><u>UPZ</u></b>	DHW circulation pump, Connection: G 1/2
	074370	<b>ZH 1</b>	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 1 A
	074371	<b>DMV / ZH 1</b>	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.

**Contact information**

You have questions? We appreciate to help you:

Call +49 5531 - 7020

Write an email to [info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.