

SBP 1010 E

HEATING BUFFER CYLINDER

PRODUCT-NO.: 236569

The SBP 1010 E – our cylinder solution for multi-storey apartment buildings.

With a permissible operating pressure of 10 bar, STIEBEL ELTRON offers an additional production solution for use in apartment buildings.



The main features

Buffer cylinder for integration into the heating system when operating a heat pump with a high output

1000 l cylinder

Specifically sized for high heat pump output, for example in the form of a cascade arrangement

WDH SBP thermal insulation as optional accessory



Type	SBP 1000 E	SBP 1010 E	SBP 1500 E
Part no.	227564	236569	227565
Rated capacity	1006 l	1006 l	1503 l
Height	2300 mm	2300 mm	2220 mm
Diameter incl. thermal insulation	1010 mm	1010 mm	1220 mm

Technical data

Heat pump flange	DN 80	DN 80	DN 80
Immersion heater flange	DN 80	DN 80	DN 80
Flanged aperture	280 mm	280 mm	280 mm
Height of unit when tilted	2335 mm	2335 mm	2250 mm
Max. permissible pressure	0,3 MPa	1 MPa	0,3 MPa
Weight	172 kg	233 kg	229 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.