

# SBP 1010 E cool

HEATING BUFFER CYLINDER

PRODUCT-NO.: 236570

**The SBP 1010 E cool – our cylinder solution for multi-storey apartment buildings.**

With a permissible operating pressure of 10 bar, STIEBEL ELTRON offers an additional production solution for use in apartment buildings. Designed for large heat pumps, it can also be used for cooling.



## The main features

Buffer cylinder for integration into the heating system when operating a heat pump with a high output

1000 l cylinder

Can be used in heating and cooling modes

Specifically sized for high heat pump output, for example in the form of a cascade arrangement

WDH SBP thermal insulation as optional accessory



Type	SBP 1000 E cool	SBP 1010 E cool	SBP 1500 E cool
<b>Part no.</b>	227588	236570	227589
<b>Rated capacity</b>	1006 l	1006 l	1503 l
<b>Height</b>	2300 mm	2300 mm	2220 mm
<b>Diameter incl. thermal insulation</b>	1010 mm	1010 mm	1220 mm

## Technical data

<b>Heat pump flange</b>	DN 80	DN 80	DN 80
<b>Immersion heater flange</b>	DN 80	DN 80	DN 80
<b>Max. permissible pressure</b>	0,3 MPa	1 MPa	0,3 MPa
<b>Flanged aperture</b>	280 mm	280 mm	280 mm
<b>Height of unit when tilted</b>	2335 mm	2335 mm	2250 mm
<b>Weight</b>	181 kg	242 kg	239 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.