

# SBP 200 E

HEATING BUFFER CYLINDER

PRODUCT-NO.: 185458

The freestanding cylinders SBP 200 to 700 E SOL are suitable as buffer cylinders for heat pump systems in detached or two-family houses. Through the integral heat exchanger, the SBP E SOL is equipped for combination with a solar thermal system. In addition, threaded electric immersion heaters can be connected. Perfect insulation ensures that the standby losses of these cylinders are remarkably low.



## The main features

Buffer cylinder for integration into the heating system

---

200 l cylinder

---

Energy efficiency class B

---

Can be used in heating and cooling modes



Type	SBP 200 E	SBP 400 E	SBP 700 E
Part no.	185458	220824	185459
Rated capacity	207 l	415 l	720 l
Height	1535 mm	1710 mm	1890 mm
Diameter incl. thermal insulation	630 mm	750 mm	910 mm

## Technical data

Energy efficiency class	B	B	
Standby energy consumption/24 h at 65 °C	1,10 kWh	1,60 kWh	2,20 kWh
Connection	4 x G2 A	4 x G2 A	4 x G2 A
Height of unit when tilted	1650 mm	1800 mm	2000 mm
Weight	58 kg	81 kg	185 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **[info@stiebel-eltron.com](mailto:info@stiebel-eltron.com)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.